

# RC-Micro 5.1



### Remarkably compact 5.1 home theater system

Delivers huge audio performance from 4 microsattellites, center channel and sub

### Heart-pounding bass performance

From 240-watt, 8-inch (20 cm) subwoofer with Ribbed Elliptical surround

### Magnetically shielded satellites, center channel

Eliminates interference with television signal

### Amazing flexibility

Keyhole slots, threaded inserts offer several mounting options

### All Energy brand components were developed with these sonic principles in mind:

- Flat On-Axis Frequency Response with Wide Bandwidth**  
 Speakers should reproduce the entire audio range in a uniform manner. By ensuring that no one frequency dominates any other, Energy ensures that every note is the way it was intended to be—and the sound is as natural as possible.
- Wide and Constant Dispersion**  
 Sound at all frequencies radiating from the speaker should be in an even pattern, in all directions throughout the room.
- Low Distortion and Resonance**  
 No speaker system is totally distortion- or resonance-free, but Energy has achieved a significantly lower distortion level—a clearly audible improvement.

SPECIFICATIONS	RC-MICRO SAT	RC-MICRO CENTER
Speaker System	Magnetically shielded acoustic suspension	
Frequency Response	150Hz-23kHz	
Tweeter	0.5-inch (12.7mm) hyperbolic aluminum dome	
Woofer	2.5-inch (63.5mm) high-excursion aluminum cone	
Crossover Point	3.5kHz	
Efficiency (Room)	88dB	
Impedance	8 Ohm compatible	
Recommended Amp. Power	20 - 100 Watts continuous	
Dimensions H x W x D	4.7 x 3.5 x 3.5 inches 12 x 9 x 9 cm	3.5 x 5.9 x 3.5 inches 9 x 15 x 9 cm
Product Weight	1.6 lbs (0.72 kg)	1.9 lbs (0.88 kg)
Inputs	Gold plated push connectors	
Finish	High gloss black	
Mounting Options	Built-in keyhole slot and threaded insert (1/4-inch - 20)	

SPECIFICATIONS	ESW-CS8
Speaker System	Bass-reflex with down firing port
Amplifier Power	240 Watts
Max SPL	97dB @ 30Hz, ground plane, 1m
Woofer	8-inch (20 cm) Injection molded cone with Ribbed Elliptical surround
Frequency Response	36Hz-180Hz
Phase Control	0°, 180°
Variable Low Pass Filter	40Hz-150Hz
Inputs	Line in/sub in, speaker level in
Power Modes	Off / Auto / On
Dimensions H x W x D (Inches/cm) including feet and grille	12.7 x 10.5 x 12.3 inches 32.2 x 40 x 31.2 cm
Product Weight	16 lbs (7.3 kg)

[www.energy-speakers.com](http://www.energy-speakers.com)