

V-MINI-C



Center Channel speaker with attractive high-end finish

High gloss black or finished rosenut cabinet

Convergent Source Module

Tweeter and woofer in proximity act as single source to increase dispersion

1-inch aluminum dome tweeter

Produces clear, accurate highs for a detailed listening experience

Dual 4.5-inch woofers with Ribbed Elliptical Surround

Deliver tight and powerful distortion-free low-frequency response

All Energy brand components were developed with these sound principles in mind:

- Flat On-Axis Frequency Response with Wide Bandwidth**
 Speakers should reproduce the entire audio range in a uniform manner. By ensuring that no one frequency dominates any other, Energy ensures that every note is the way it was intended to be – and the sound is as natural as possible.
- Wide and Constant Dispersion**
 Sound at all frequencies radiating from the speakers should be in an even pattern, in all directions throughout the room.
- Low Distortion and Resonance**
 No speaker system is totally distortion- or resonance-free, but Energy has achieved a significantly lower distortion level – a clearly audible improvement.

SPECIFICATIONS	V-MINI-C
Speaker System	2 way center channel loudspeaker with shielded drivers, rear vented bass reflex design
Frequency Response	78Hz-25kHz ± 3dB
Recommended Amp. Power	up to 150 watts RMS
Sensitivity	93.5dB
Impedance	8 ohms nominal; 4 ohms minimum
Tweeter	One 1" tweeter with aluminum dome and neodymium motor
Woofers	Two 4.5" woofers with kevlar cone and Ribbed Elliptical Surround
Crossover Point	2.5kHz
Inputs	Single 5-way nickel-plated binding post
Height	4.72" (12cm)
Width	13.78" (35cm)
Depth	5.51" (14cm)
Weight	9 lbs / 4.1 kg
Finish	High Gloss Black & Finished Rosenut
Included Accessories	Rubber bumpers