

TAKE CLASSIC

Bold and Beautiful 5.1 Home Theater System

System features superior MDF cabinets finished in high-gloss black to look good and sound great

Heart-Pounding Bass Performance

200-watt, 8-inch (20 cm) subwoofer with Ribbed Elliptical Surround™

Smooth, Realistic Sound

Each speaker utilizes a Convergent Source Module with 3-inch (7.6 cm) poly-titanium woofer and ¾-inch (19 mm) Hyperbolic™ aluminum-dome tweeter for a dynamic frequency range and an expansive soundstage

Amazing Flexibility

Keyhole slots, threaded inserts, and rubber bumpers offer several mounting options



SPECIFICATIONS	Sat	Center
System Type	Magnetically Shielded Bass Reflex with Rear Firing Port	Magnetically Shielded Bass Reflex with Dual Front Firing Ports
Frequency Response (+/- 3 dB)	115Hz-20KHz	110Hz-20KHz
Tweeter	³4-inch (19 mm) Hyperbolic™ aluminum-dome tweeter	³¼-inch (19 mm) Hyperbolic™ aluminum-dome tweeter
Woofer	3-inch (7.6 cm) poly-titanium	3-inch (7.6 cm) poly-titanium
Crossover Point	2.9 kHz	2.9 kHz
Efficiency (Room)	89 dB	89 dB
Impedance	8-ohm compatible	8-ohm compatible
Maximum Power Handling	100 Watts	100 Watts
Recommended Amplifier Power	20 - 100 Watts RMS (Continous)	20 - 100 Watts RMS (Continous)
Dimensions HxWxD (grille not included)	inches: 6 7/8 x 4 1/8 x 4 1/8 mm: 169 x 105 x 105	inches: 4 1/8 x 10 1/4 x 4 1/8 mm: 105 x 260 x 105
Weight	2.9 lb / 1.32 kg	3.2 lb / 1.45 kg
Colors	High Gloss Black	High Gloss Black
Inputs	Mini 5-Way Binding Posts	Mini 5-Way Binding Posts
Mounting Options	Built-in keyhole slot and threaded insert (1/4" - 20 TPI) to accept articulating brackets such as Omni Mount	

System Type Bass Reflex with Front Port Amplifier Power Output 200 Watts 8" (20 cm) IM Cone with Patented Ribbed Elliptic Surround Frequency Response 33Hz-150Hz +/- 3dB Variable Phase Control 0°, 180° Variable Low Pass Filter 40Hz-150Hz @ 18dB/o Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) add 2 1/16" (52.4mm) for feet	
Woofer 8" (20 cm) IM Cone with Patented Ribbed Ellipt Surround Frequency Response 33Hz-150Hz +/- 3dB Variable Phase Control 0°, 180° Variable Low Pass Filter 40Hz-150Hz @ 18dB/o Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x 12	Firing
Woofer Patented Ribbed Ellipt Surround Frequency Response 33Hz-150Hz +/- 3dB Variable Phase Control 0°, 180° Variable Low Pass Filter 40Hz-150Hz @ 18dB/o Inputs Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x	
Variable Phase Control 0°, 180° Variable Low Pass Filter 40Hz-150Hz @ 18dB/o Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x	
Variable Low Pass Filter 40Hz-150Hz @ 18dB/o Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x 12 5/8	
Inputs Line In/Sub In & Speak Level In Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x 1	
Power Mode Switch On/Auto/Off Dimensions HxWxD (feet not included) inches: 12 5/8 x 12 5/8	ctave
Dimensions HxWxD (feet not included) inches: 12 5/8 x 12 5/8 mm 230 7 x 230 7 x 230	ær
(feet not included) Inches: 12 5/8 x 12 5/8	
Weight 19.7 lbs. / 8.94 kg.	
Colors High Gloss Black	