

V-6.2



Floorstanding speaker with attractive high-end finish

High gloss piano black or rosenut cabinet

Convergent Source Module

Tweeter and woofer in proximity act as single source to increase dispersion

1-inch aluminum dome tweeter

Produces clear, accurate highs for a detailed listening experience

Dual 6.5-inch woofers with Ribbed Elliptical Surround

Deliver tight and powerful distortion-free low-frequency response

All Energy brand components were developed with these sound principles in mind:

- Flat On-Axis Frequency Response with Wide Bandwidth**
 Speakers should reproduce the entire audio range in a uniform manner. By ensuring that no one frequency dominates any other, Energy ensures that every note is the way it was intended to be – and the sound is as natural as possible.
- Wide and Constant Dispersion**
 Sound at all frequencies radiating from the speakers should be in an even pattern, in all directions throughout the room.
- Low Distortion and Resonance**
 No speaker system is totally distortion-or resonance-free, but Energy has achieved a significantly lower distortion level – a clearly audible improvement.

SPECIFICATIONS	V-6.2
Speaker System	2.5 way floorstanding loudspeaker with shielded drivers, rear vented bass reflex design
Frequency Response	33Hz-25kHz ± 3dB
Recommended Amplifier Power	up to 225 watts RMS
Sensitivity	92dB
Impedance	8 ohms nominal; 4 ohms minimum
Tweeter	One 1" tweeter with aluminum dome and neodymium motor with heat sink
Woofers	Two 6.5" woofers with kevlar cones and Ribbed Elliptical Surrounds
Crossover Points	700Hz, 1.9kHz
Inputs	Dual 5-way nickel-plated binding posts
Height	40.24" (102.2cm)
Width	7.76" (19.7cm)
Depth	14.06" (35.7cm)
Weight	49.5 lbs / 22.5 kg
Finish	Piano Black & Piano Rosenut
Included Accessories	Spike kit, rubber bumpers, high gloss black base/plinth, port plugs